

VP 415



WARNING STRIPE TAPE



TYPICAL APPLICATIONS

- For lane marking and identification of safety zones and hazard areas

PRODUCT FEATURES

- Resistant to abrasion, UV light, acid, alkalides, oils, moisture, humidity and corrosion
- Meets OSHA requirements for hazard markings

CONSTRUCTION

Overall Grade/Function: General purpose

Backing: Striped, stabilized, plasticized, soft polyvinylchloride film (SPVC)

Adhesive: Natural rubber

STANDARD WIDTH(S)

50 mm

STANDARD LENGTH(S)

30 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A-1689B, Type 1, Class 2

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



BLACK/YELLOW
(BKY)



BLACK/WHITE
(BKW)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	15 lbs/in width	26.3 N/10 mm
Adhesion to Stainless Steel	12 oz/in width	1.31 N/10 mm
Thickness	6.6 mils	0.17 mm
Elongation	200%	200%
Service Temperature Range	20 F to 140 F	-7 C to 60 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

