

PP 815



HEAVY DUTY GRADE SOLVENT-BASED ACRYLIC PACKAGING TAPE



TYPICAL APPLICATIONS

- For critical sealing and repairing of corrugated containers in hot and cold environments
- Use with a hand-held dispenser

PRODUCT FEATURES

- Excellent impact and shear resistance
- Performs in a range of temperatures
- Excellent aging characteristics
- High tack

CONSTRUCTION

Overall Grade/Function: Heavy duty
Backing: 40 micron biaxially oriented polypropylene cast film
Adhesive: Solvent-based acrylic

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	28 oz/in width	3.06 N/10 mm
Adhesion to Backing	18 oz/in width	1.97 N/10 mm
Adhesion to Kraft	16 oz/in width	1.75 N/10 mm
Thickness	2.6 mils	0.066 mm
Elongation	140%	140%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

